

Safety Data Sheet P-4602

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.Issue date: 01/01/1979Revision date: 01/25/2022Supersedes: 05/20/2021Version: 2.2

SECTION: 1. Product and company ic	dentification
1.1. Product identifier	
Product form	: Substance
Trade name	: Helium, LaserStar Helium, Medipure Helium, UltraLift Helium
Chemical name	: Helium
CAS-No.	: 7440-59-7
Formula	: He
Other means of identification	: Helium-4, refrigerant gas R-704, LaserStar Helium, Medipure Helium, UltraLift Helium, Helium - Diving Grade
1.2. Relevant identified uses of the subst	ance or mixture and uses advised against
Use of the substance/mixture	: Industrial use Medical applications. Diving Gas (Underwater Breathing)
1.3. Details of the supplier of the safety d	ata sheet
	Linde Inc. 10 Riverview Drive Danbury, CT 06810-6268, USA www.lindeus.com Linde Inc. 1-844-44LINDE (1-844-445-4633)
	Einde inc. 1 - 0 + 4 - 4 + Einde (1 - 0 + 4 - 4 + 3 - 4 + 0 - 5)
1.4. Emergency telephone number	
Emergency number	: Onsite Emergency: 1-800-645-4633
	CHEMTREC, 24hr/day 7days/week — Within USA: 1-800-424-9300, Outside USA: 001-703-527-3887 (collect calls accepted, Contract 17729)
SECTION 2: Hazard identification	
2.1. Classification of the substance or mi	xture
GHS US classification	
Simple asphyxiant SIAS Press. Gas (Comp.) H280	
2.2. Label elements	
GHS US labeling	
Hazard pictograms (GHS US)	: GHS04
Signal word (GHS US)	: Warning
Hazard statements (GHS US)	: H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED OSHA-H01 - MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.
Precautionary statements (GHS US)	<ul> <li>P202 - Do not handle until all safety precautions have been read and understood.</li> <li>P271 - Use and store only outdoors or in a well-ventilated area.</li> <li>P403 - Use and store only outdoors or in a well-ventilated place.</li> <li>P304, P340, P313 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.</li> <li>CGA-PG05 - Use a back flow preventive device in the piping.</li> <li>CGA-PG10 - Use only with equipment rated for cylinder pressure.</li> <li>CGA-PG12 - Do not open valve until connected to equipment prepared for use.</li> </ul>

EN (English US)

SDS ID: P-4602



Safety Data Sheet P-4602 This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 01/25/2022 Supersedes: 05/20/2021 Issue date: 01/01/1979

CGA-PG06 - Close valve after each use and when empty.

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).

Version: 2.2

2.3.	Other hazards			
Other ha		: Asphyxiant in high concentra	itions.	
2.4.	Unknown acute toxicity (GHS US)			
		No data available		
SECTI	ON 3: Composition/Information	on ingredients		
3.1.	Substances			
Name	:	: Helium, compressed		
CAS-No		: 7440-59-7		
Name		Product identifier	%	
Helium		(CAS-No.) 7440-59-7	99.5 – 100	
3.2.	Mixtures			
Not appl	icable			
SECTI	ON 4: First aid measures			
4.1.	Description of first aid measures			
First-aid	measures after inhalation			comfortable for breathing. If not breathing, ined personnel should give oxygen. Call a
First-aid	measures after skin contact	Adverse effects not expected	from this product.	
First-aid	measures after eye contact	: Adverse effects not expected plenty of water. Consult an o		case of eye irritation: Rinse immediately with tion persists.
First-aid	measures after ingestion	: Ingestion is not considered a potential route of exposure.		
4.2.	Most important symptoms and effects	s, both acute and delayed		
		No additional information ava	ailable	
4.3.	Indication of any immediate medical a	ttention and special treatme	nt needed	
None.				
SECTI	ON 5: Firefighting measures			
5.1.	Extinguishing media			
Suitable	extinguishing media	: Use extinguishing media app	propriate for surroundi	ng fire.
5.2.	Special hazards arising from the subs	stance or mixture		
No addit	ional information available			
5.3.	Advice for firefighters			
Firefighti	ing instructions	and protective clothing. Imm flow of gas if safe to do so, w safe to do so. Remove conta	ediately cool containe hile continuing cooling iners from area of fire	e self-contained breathing apparatus (SCBA) ers with water from maximum distance. Stop g water spray. Remove ignition sources if if safe to do so. On-site fire brigades must ole standards under 29 CFR 1910 Subpart
Protectio	on during firefighting	: Compressed gas: asphyxian	t. Suffocation hazard I	by lack of oxygen.
Special	protective equipment for fire fighters	: Use self-contained breathing Contained Breathing Appara		protective clothing and equipment (Self



Safety Data Sheet P-4602

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.Issue date: 01/01/1979Revision date: 01/25/2022 Supersedes: 05/20/2021Version: 2.2

Specific methods

: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas containers to rupture. Cool endangered containers with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.

Stop flow of product if safe to do so.

Use water spray or fog to knock down fire fumes if possible.

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective equipment and emergency procedures			
General	measures :	Evacuate area. Ensure adequate air ventilation. Wear self-contained breathing apparatus when entering area unless atmosphere is proven to be safe. Stop leak if safe to do so.	
6.1.1.	For non-emergency personnel	No additional information available	
6.1.2.	For emergency responders	No additional information available	
6.2.	Environmental precautions		
		Try to stop release.	
6.3.	Methods and material for containment	and cleaning up	
		No additional information available	
6.4.	Reference to other sections		
		See also sections 8 and 13.	
SECTI	ON 7: Handling and storage		
7.1.	Precautions for safe handling		
Precautio	ons for safe handling :	Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g, wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.	
Safe use	of the product :	The suitability of this product as a component in underwater breathing gas mixtures is to be determined by or under the supervision of personnel experienced in the use of underwater breathing gas mixtures and familiar with the physiological effects, methods employed, frequency and duration of use, hazards, side effects, and precautions to be taken.	
7.2.	Conditions for safe storage, including	any incompatibilities	
Storage	conditions :	Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods.	
		<b>OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE:</b> When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.	

EN (English US)

3/9



Safety Data Sheet P-4602 This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Revision date: 01/25/2022 Supersedes: 05/20/2021 Issue date: 01/01/1979 Version: 2.2

7.3. Specific end use(s)

None.

SECTION 8: Exposur	e controls/personal protection
8.1. Control parameter	· ·
Helium, compressed (74	10-59-7)
ACGIH	Not established
USA OSHA	Not established
Helium (7440-59-7)	
ACGIH	Not established
USA OSHA	Not established
B.2. Exposure contro	ls la
Appropriate engineering cor	trols : Use a local exhaust system with sufficient flow velocity to maintain an adequate supply of air in the worker's breathing zone. Mechanical (general): General exhaust ventilation may be acceptable if it can maintain an adequate supply of air.
Eye protection	: Wear safety glasses with side shields.
Skin and body protection	: Wear metatarsal shoes and work gloves for cylinder handling, and protective clothing where needed. Wear appropriate chemical gloves during cylinder changeout or wherever contact with product is possible. Select per OSHA 29 CFR 1910.132, 1910.136, and 1910.138.
Respiratory protection	: When workplace conditions warrant respirator use, follow a respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).

<b>SECTION 9: Physical and chemica</b>	l properties	
9.1. Information on basic physical and	I chemical properties	
Physical state	: Gas	
Appearance	: Colorless gas.	
Molecular mass	: 4 g/mol	
Color	: Colorless.	
Odor	: Odorless.	
Odor threshold	: No data available	
рН	: Not applicable.	
Relative evaporation rate (butyl acetate=1)	: No data available	
Relative evaporation rate (ether=1)	: Not applicable.	
Melting point	: -272 °C	
Freezing point	: No data available	
Boiling point	: -268.93 °C	
Flash point	: No data available	
Critical temperature	: -268 °C	
Auto-ignition temperature	: Not applicable.	
Decomposition temperature	: No data available	
Flammability (solid, gas)	: No data available	
Vapor pressure	: Not applicable.	
Critical pressure	: 230 kPa	
Relative vapor density at 20 °C	: No data available	
Relative density	: No data available	
Density	: 0.166 kg/m <sup>3</sup>	
EN (English US)	SDS ID: P-4602	4/9



Safety Data Sheet P-4602 This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Revision date: 01/25/2022 Supersedes: 05/20/2021 Issue date: 01/01/1979 Version: 2.2

	Issue date: 01/01/1979	Revision date: 01/25/2022 Supersedes: 05/20/2021	Version: 2.2
Relative gas density         Solubility         Partition coefficient n-octanol/wat         Partition coefficient n-octanol/wat         Viscosity, kinematic         Viscosity, dynamic         Explosive properties         Oxidizing properties         Explosion limits         9.2.       Other information			
Gas group Additional information	: Compressed g : None.	as	
SECTION 10: Stability an 10.1. Reactivity	d reactivity		
	No additional in	nformation available	
10.2. Chemical stability		ormal conditions.	
10.3. Possibility of hazardo			
10.3. Possibility of hazardo	None.		
10.4. Conditions to avoid		nomenand atoms and bandling conditions (and position -	7)
40.5 Is a supervisit to supervise		commended storage and handling conditions (see section 7	·).
10.5. Incompatible material	None.		
10.6. Hazardous decompos			
	None.		
SECTION 11: Toxicologic	cal information		
11.1. Information on toxico			
Acute toxicity	: Not classified		
Skin corrosion/irritation	: Not classified		
Serious eye damage/irritation	pH: Not applicat : Not classified pH: Not applicat		
Respiratory or skin sensitization	: Not classified		
Germ cell mutagenicity	: Not classified		
Carcinogenicity	: Not classified		
Reproductive toxicity STOT-single exposure	: Not classified : Not classified		
STOT-repeated exposure	: Not classified		
Aspiration hazard	: Not classified		
SECTION 12: Ecological	information		
12.1. Toxicity			
Ecology - general	: No ecological	damage caused by this product.	
EN (English LIS)		SDS ID: P-4602	F

SDS ID: P-4602



Safety Data Sheet P-4602 This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 01/25/2022 Supersedes: 05/20/2021 Issue date: 01/01/1979 Version: 2.2

12.2. Persistence and degradability		
Helium, compressed (7440-59-7)		
Persistence and degradability	No ecological damage caused by this product.	
Helium (7440-59-7)		
Persistence and degradability	No ecological damage caused by this product.	
12.3. Bioaccumulative potential		
Helium, compressed (7440-59-7)		
Partition coefficient n-octanol/water (Log Pow)	Not applicable.	
Partition coefficient n-octanol/water (Log Kow)	Not applicable.	
Bioaccumulative potential	No ecological damage caused by this product.	
Helium (7440-59-7)		
Partition coefficient n-octanol/water (Log Pow)	Not applicable for inorganic gases.	
Partition coefficient n-octanol/water (Log Kow)	Not applicable.	
Bioaccumulative potential	No ecological damage caused by this product.	
12.4. Mobility in soil		
Helium, compressed (7440-59-7)		
Mobility in soil	No data available.	
Ecology - soil	No ecological damage caused by this product.	
Helium (7440-59-7)		
Mobility in soil	No data available.	
Ecology - soil	No ecological damage caused by this product.	
12.5. Other adverse effects		
Effect on ozone layer	: None.	
-	: None.	
noor on the global warming		

SECTION 13: Disposal consideration	IS
13.1. Waste treatment methods	
Product/Packaging disposal recommendations	: Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.
<b>SECTION 14: Transport information</b>	
In accordance with DOT	

Transport document description (DOT)	: UN1046 Helium, compressed, 2.2
UN-No.(DOT)	: UN1046
Proper Shipping Name (DOT)	: Helium, compressed
Class (DOT)	: 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115
Hazard labels (DOT)	: 2.2 - Non-flammable gas

	•
Additional information	
Emergency Response Guide (ERG) Number	: 120 (UN1963)
Other information	: No supplementary information available.

SDS ID: P-4602



Safety Data Sheet P-4602

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.Issue date: 01/01/1979Revision date: 01/25/2022Supersedes: 05/20/2021Version: 2.2

Special transport precautions

Transport by sea

: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Transport by sea	
UN-No. (IMDG)	: 1046
Proper Shipping Name (IMDG)	: HELIUM, COMPRESSED
Class (IMDG)	: 2 - Gases
Division (IMDG)	: 2.2 - Non-flammable, non-toxic gases
MFAG-No	: 121
Air transport	
UN-No. (IATA)	: 1046
Proper Shipping Name (IATA)	: Helium, compressed
Class (IATA)	: 2 - Gases
Civil Aeronautics Law	: Gases under pressure/Gases nonflammable nontoxic under pressure

### **SECTION 15: Regulatory information**

15.1. US Federal regulations

### Helium, compressed (7440-59-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory.

#### 15.2. International regulations CANADA

#### Helium, compressed (7440-59-7)

Listed on the Canadian DSL (Domestic Substances List)

#### Helium (7440-59-7)

Listed on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

#### Helium, compressed (7440-59-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### 15.2.2. National regulations

#### Helium, compressed (7440-59-7)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on KECL/KECI (Korean Existing Chemicals Inventory) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on the TCSI (Taiwan Chemical Substance Inventory)

SDS ID: P-4602



Safety Data Sheet P-4602

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 01/25/2022 Supersedes: 05/20/2021 Issue date: 01/01/1979

Version: 2.2

15.3. US State regulations	
Helium, compressed(7440-59-7)	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

### Helium (7440-59-7)

U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	No	No	No		
Helium (7440-59-7)					

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List



Safety Data Sheet P-4602 This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Revision date: 01/25/2022 Supersedes: 05/20/2021 Issue date: 01/01/1979 Version: 2.2

SECTION 16: Other information				
Other information	: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.			
	Linde asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.			
	The opinions expressed herein are those of qualified experts within Linde Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Linde Inc, it is the user's obligation to determine the conditions of safe use of the product.			
	Linde SDSs are furnished on sale or delivery by Linde or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your sales representative, local distributor, or supplier, or download from www.lindeus.com. If you have questions regarding Linde SDSs, would like the document number and date of the latest SDS, or would like the names of the Linde suppliers in your area, phone or write the Linde Call Center (Phone: 1-844-44-Linde (1-844-445-4633); Address: Linde Call Center, Linde Inc, P.O. Box 44, Tonawanda, NY 14151-0044).			
	Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.			
	Copyright © 2021, Linde Inc.			
Revision date	: 01/25/2022			
NFPA health hazard	: 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.			
NFPA fire hazard	: 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.			
NFPA instability	: 0 - Material that in themselves are normally stable, even under fire conditions.			
NFPA specific hazard	: SA - This denotes gases which are simple asphyxiants.			

SDS US (GHS HazCom 2012) - Linde 2022

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.